

Automotive Interiors

A practical care reference for island conditions

Routine cleaning Vacuum seats and seams, wipe spills promptly and use a soft cloth. Remove sand and grit that can abrade high-wear entry areas.	Approved cleaner types Choose a product labeled for the installed automotive vinyl, fabric or leather substitute. Apply to the cloth rather than flooding the seat.
Products to avoid Avoid bleach, solvents, oily dressings, abrasive pads and heavy saturation near seams, electronics or occupancy sensors.	Drying and ventilation Leave doors or windows safely open for airflow after cleaning. Ensure carpet, padding and seat foam are dry before prolonged closure.
Mold or mildew precautions Investigate leaks and wet carpet promptly. Cleaning the surface alone will not solve moisture trapped in padding or foam.	Sun and moisture exposure Use windshield shade and ventilation when practical. Heat and UV can fade surfaces and accelerate cracking or adhesive failure.
When to contact Chung Nam Call for torn bolsters, sagging foam, loose headliners, persistent dampness, odors, failed seams or water intrusion.	

Manufacturer care and warranty limitations

This guide provides general care guidance only. The installed material's manufacturer instructions, cleaning code and warranty control. Spot-test products, keep product labels and project records, and contact Chung Nam before using a treatment that is not specifically approved. Damage from misuse, harsh chemicals, contamination, extreme weather or unresolved moisture may not be covered by a material or workmanship warranty.

Need help? Send a photo and the project name or invoice information to Chung Nam before attempting aggressive cleaning or repair.